

# **SK LINE 79**

₩AMS ₩DPS-2 Offshore Support Vessel

Malaysia

9680683

335589

9MQZ3

1356 Tonnes

186 m<sup>3</sup>

2015

Port Kelang

**VESSEL PARTICULARS** 

Class

Flag

P.O.R

**Year Built** 

Builder

IMO

## 59.25M ANCHOR HANDLING TOWING SUPPLY VESSEL 65 T BOLLARD PULL | DP2 | FIFI 1



## Official Number Call Sign

**DIMENSION** 

L.O.A. 59.25 m Beam 14.95 m Depth 6.10 m Draft (max) 4.95 m GRT 1679 NRT 503

## **CARGO CAPACITIES**

Deadweight

Deck Cargo 500 Tonnes **Deck Loading** 7.5 Tonnes/m<sup>2</sup> Deck Area 330 m<sup>2</sup> Fresh Water 301 m<sup>3</sup> Drill/Bal Water 401 m<sup>3</sup> Fuel Oil 527 m<sup>3</sup> Mud 378 m<sup>3</sup> 166 m<sup>3</sup> **Brine** 

#### **ACCOMMODATION**

**Dry Bulk** 

1 Man cabin 4x 1 (4) 2 Men Cabin 3x 2 (6) 4 Men cabin 8x 4 (32) Total 42 berths Hospital 1 berth

## **PERFORMANCE**

Speed 12.0 knots **Bollard Pull (measured)** 68.2 tonnes

## **PROPULSION & POWER PLANT**

**Propellers** 2x 1920KW Conventional CPP **Bow Thruster** 2x 515KW, 8T Thrust each **Stern Thruster** 1x 390KW, 6T Thrust each **Main Engine** 2x 1920KW 1600 rpm **Main Generator** 3x 350KW, 415V3Ph50Hz **Shaft Generator** 2x 800KW, 415V3Ph50Hz **Emerg Generator** 1x 65KW, 415V3Ph50Hz

#### **DECK MACHINERY**

2x 10 Tonnes SWL **Tugger winch** 2x 5 Tonnes SWL Capstan

**Provision Crane** 1x 3 Tonnes SWL @ 9 m radius

**AHT Winch** 1x Electro-Hydraulic Double Drum AH/T Winch

> Line pull: 150 Tonnes Brake: 200 Tonnes

Drum cap: 1000m x 56mm dia. Wire

**Storage Reel** 1x 1000m x 56mm dia. Wire

**Shark Jaw** 1x 200 Tonnes SWL **Towing Pins** 1x 200 Tonnes SWL

Stern Roller 1x 4m(L) x 1.6m(dia.) 200Tonnes SWL


#### **CARGO HANDLING CAPACITY**


Fresh Water 1x 125 m<sup>3</sup>/hr @ 75 m head **Drill Water** 1x 100 m<sup>3</sup>/hr @ 75 m head **Fuel Oil** 1x 150 m<sup>3</sup>/hr @ 75 m head Mud 2x 75 m<sup>3</sup>/hr @ 75 m head Brine 1x 75 m<sup>3</sup>/hr @ 75 m head 2x 13 m<sup>3</sup>/min @ 5.6 bar **Dry Bulk** 


Water Maker 1x 5 m<sup>3</sup>/day



## SK LINE 79 | 59.25M ANCHOR HANDLING TOWING SUPPLY VESSEL







BRIDGE DECK PLAN

THIS DRAWING AND THE INFORMATION CONTAINED HEREIN ARE SUPPLIED ON THE UNDERSTANDING THAT THEY ARE THE EXCLUSIVE PROPERTY OF KINAM CHUAN MARINE PTE LTD. THEY MUST NOT BE USED OR REPRODUCED IN WHOLE OR IN PART WITHOUT PERMISSION IN WRITING.

#### **NAVIGATION EQUIPMENT**

Radars, Magnetic Compass, Gyro Compasses, DGPSs, AIS Autopilot, Echo Sounder, Speed Log, Navtex, Weather Fax SSAS, BNWAS

## **COMMUNICATION EQUIPMENT**

GMDSS A1+A2+A3, VSAT

#### FIRE-FIGHTING EQUIPMENT

External FiFi Pump: 2x 1650 m<sup>3</sup>/hr @ 120m

Monitor: 1x 1200 m<sup>3</sup>/hr (water/foam)

Monitor: 1x 1200 m<sup>3</sup>/hr (water)

Oil Dispersant 2x 6m spray booms with nozzles

#### **SAFETY EQUIPMENT**

Rescue Boat 1x 6 men Rescue Boat

## **SKOM SDN BHD** (1182610-K)

B-03-B-17-1, Menara 3A, No.3, Jalan Bangsar, KL Eco City, 59200 Kuala Lumpur, Malaysia Tel: +603-2280 6777 | Fax: +603-2201 7778 | www.skom.com.my

\*Disclaimer: All information provide here is accurate at the time of printing and may be subjected to change without prior notice. While every reasonable care has been taken in preparing this document, SKOM Sdn Bhd. Will not be held responsible for any inaccuracies.