

SK MAGNITUDE

VESSEL PARTICULARS

C

| Class | ABS ₩A1 🕑 SPS ₩AMS |
|-----------------|-------------------------------|
| | Offshore Support Vessel FFV 1 |
| | ∯DPS-2 CRC RW |
| Flag | Malaysia |
| P.O.R | Port Kelang |
| Year Built | 2018 |
| Builder | Xiamen Shipbuilding Industry |
| IMO | 9753856 |
| Official Number | 335809 |
| Call Sign | 9MWC3 |
| | |

DIMENSION

| L.O.A. | 78.00 m |
|-------------|---------|
| Beam | 20.00 m |
| Depth | 8.00 m |
| Draft (max) | 6.40 m |
| GRT | 4951 |
| NRT | 1485 |

CARGO CAPACITIES

Deadweight 3618 Tonnes Deck Cargo 1000 Tonnes Deck Loading 10 Tonnes/m² Deck Area 750 m² Fresh Water 1168 m³ Drill/Bal Water 2433 m³ 1481 m³ Fuel Oil

ACCOMMODATION

| 1 Man cabin | 6x 1 (6) |
|-------------|-------------|
| 2 Men Cabin | 19x 2 (38) |
| 4 Men cabin | 39x 4 (156) |
| Total | 200 berths |
| Hospital | 2 berths |

PERFORMANCE

Speed 11.5 knots

78M MAINTENANCE WORK VESSEL 200 MEN | DP 2 | FIFI 1



PROPULSION & POWER PLANT

| 2x 2206KW Azimuth Thrusters |
|-----------------------------|
| 2x 785KW, 12T Thrust each |
| 2x 2206KW 800 rpm |
| 2x 715KW, 440V3Ph60Hz |
| 2x 1236KW, 440V3Ph60Hz |
| 1x 150KW, 440V3Ph60Hz |
| |

DECK MACHINERY


| Tugger winch | 2x 10 Tonnes SWL |
|------------------|---|
| Capstan | 2x 5 Tonnes SWL |
| Provision Crane | 1x 3 Tonnes SWL @ 12 m radius |
| 4 Points Mooring | 4x Electro-Hydraulic Mooring Winches |
| | Line pull: 50 Tonnes |
| | Brake: 120 Tonnes |
| | Drum cap: 1500m x 42mm dia. Wire |
| | 4x 5 Tonnes Delta Flipper Anchors |
| Pedestal Crane | 1x 50 Tonnes @ 12 m radius |
| | Boom Length: 36.6m lattice type |
| | API 2C, certified for Personnel Lifting |


CARGO HANDLING CAPACITY


| Fresh Water | 1x 120 m ³ /hr @ 90 m head |
|-------------|---------------------------------------|
| Drill Water | 1x 120 m³/hr @ 90 m head |
| Fuel Oil | 1x 120 m ³ /hr @ 90 m head |
| Water Maker | 2x 40 m³/day |




SK MAGNITUDE | 78M MAINTENANCE WORK VESSEL










THIS DRAWING AND THE INFORMATION CONTAINED HEREIN ARE SUPPLIED ON THE UNDERSTANDING THAT THEY ARE THE EXCLUSIVE PROPERTY OF FOCAL MARINE & OFFSHORE. THEY MUST NOT BE USED OR REPRODUCED IN WHOLE OR IN PART WITHOUT PERMISSION IN WRITING.



FIRE-FIGHTING EQUIPMENT

| External FiFi | Pump: 2x 1830 m³/hr @ 120m |
|-----------------------|--|
| | Monitor: 1x 1200 m ³ /hr (water/foam) |
| | Monitor: 1x 1200 m ³ /hr (water) |
| Oil Dispersant | 2x 6m spray booms with nozzles |
| | |
| | |

SAFETY EQUIPMENT

| Rescue Boat |
|-------------|
| Lifeboat |

2x 6 men Fast Rescue Boat 118 KW in board engine, waterjet 2x 100 men Life Boats

SKOM SDN BHD (1182610-K)

B-03-B-17-1, Menara 3A, No.3, Jalan Bangsar, KL Eco City, 59200 Kuala Lumpur, Malaysia Tel : +603-2280 6777 | Fax: +603-2201 7778 | www.skom.com.my

* Disclaimer : All information provide here is accurate at the time of printing and may be subjected to change without prior notice. While every reasonable care has been taken in preparing this document, SKOM Sdn Bhd. Will not be held responsible for any inaccuracies.

NAVIGATION EQUIPMENT

Radars, Magnetic Compass, Gyro Compasses, DGPSs, AlS Autopilot, Echo Sounder, Speed Log, Navtex, Weather Fax SSAS, BNWAS, (VDR), (ECDIS)

COMMUNICATION EQUIPMENT

GMDSS A1+A2+A3, VSAT