

SK PARTNER

60M ANCHOR HANDLING TUG SUPPLY VESSEL 60T BP \mid 5150 BHP \mid DP1 \mid FIFI 1 \mid 42 MEN \mid 330 m²



VESSEL PARTICULARS

Class BV I Tug Supply vessel Fire

fighting ship 1 -water spraying Special service Special Service — Anchor

Handling

Flag Malaysia P.O.R Port Kelang

Year Built 2011

Builder Fujian Southeast Shipyard

 IMO
 9587271

 Official Number
 334278

 Call Sign
 9MLM8

DIMENSION

 L.O.A.
 59.25 m

 Beam
 14.90 m

 Depth
 6.10 m

 Draft (max)
 4.95 m

 GRT
 1678 Tonnes

 NRT
 503 Tonnes

CARGO CAPACITIES

Deadweight1353 TonnesDeck Cargo500 TonnesDeck Loading7.5 Tonnes/m²

 Deck Area
 330 m²

 Fresh Water
 373 m³

 Drill/Ballast Water
 401 m³

 Fuel Oil
 527 m³

 Mud
 378 m³

 Dry Bulk
 186 m³

ACCOMMODATION

 1 Man Cabin
 4x 1 (4)

 2 Men Cabin
 3x 2 (6)

 4 Men Cabin
 8x 4 (32)

 Total
 42 berths

 Hospital
 1 berth

PERFORMANCE

Speed 10 knots Bollard Pull 63 Tonnes

PROPULSION & POWER PLANT

Propellers Conventional CPP

Bow Thruster 1x 515kW, 8T Thrust each

Main Engine 2 x 2575 BHP 3516B-HD Caterpillar

Main Generator 2x 350kW, CAT C18

Shaft Generator 2x 800kW Leroy Somer M44.2VS3C6/4

Emerg Generator 1x 75Kw Caterpillar C4.4

DECK MACHINERY

Tugger winch2x 10 Tonnes SWLCapstan2x 5 Tonnes SWL

Provision Crane 1x 3 Tonnes SWL @ 8 m radius

AHT Winch 1x Electro-Hydraulic Double Drum AH/T

Winch

Line pull: 150 Tonnes Brake: 200 Tonnes

Drum cap: 1000m x 56mm dia. Wire

Storage Reel 1x 1000m x 56mm dia. Wire

Shark Jaw 1x 200 Tonnes SWL
Towing Pins 2x 200 Tonnes SWL

Stern Roller 1x 4m(L) x 1.6m(dia.) 200Tonnes SWL

CARGO HANDLING CAPACITY

 Fresh Water
 1x 125 m³/hr @ 75 m head

 Drill Water
 1x 100 m³/hr @ 75 m head

 Fuel Oil
 1x 150 m³/hr @ 75 m head

 Mud
 2x 70 m³/hr @ 75 m head


 Dry Bulk
 2x 13 m³/min @ 5.6 bar


Water Maker 1x 5 MT/day





SK PARTNER | 60M ANCHOR HANDLING TUG SUPPLY VESSEL









A			59m#####			CONSTRUCTION DESCRIPTION		
H + H			TUO SUPPLY MISSEL			50032-100-01		
A	-	-	┲	总布里图		DMSSW-80/81 A####CJASS: ARS		
(大)		_	1					
-	400 4.5 5		CENERAL ARRANCEMENT		BERRY.	thus h	6# 5X	
** 139	-	-	00	OUNCE HITTINGS		84	_	1:150
en one			1	1			RK.4 # 1	
44 (MIC 1 (D))						福建	2 8 4	造船厂

NAVIGATION EQUIPMENT

Radars, Magnetic Compass, Gyro Compasses, DGPSs, AIS Autopilot, Echo Sounder, Speed Log, Navtex, Weather Fax, SART

COMMUNICATION EQUIPMENT

GMDSS A1+A2+A3, VSAT

FIRE-FIGHTING EQUIPMENT

External FiFi Pump: 2x 1400 m³/hr

Monitor: 2x 1200 m³/hr

Oil Dispersant 2x 6m spray booms with nozzles

SAFETY EQUIPMENT

Rescue Boat 1x 6 men Rescue Boat

SKOM SDN BHD (1182610-K)

B03-B-17-1, Menara 3A, No.3, Jalan Bangsar, KL Eco City, 59200 Kuala Lumpur, Malaysia Tel: +603-2280 6777 | Fax: +603-2201 7778 | www.skom.com

Disclaimer: All information provided here is accurate at the time of printing and may be subject to change without prior notice. While every reasonable care has been taken in preparing this document. SKOM Sdn Bhd will not be held responsible for any inaccuracies.